



ALL-IN-ONE COMPRESSORS

GLA 2 - 7 series
Fixed Speed
Regulated Speed (RS)



www.geveke.com



The all-in-one compressor

Advanced screw air end

The GLA and GLA RS comes with a new air end that delivers more air efficiently.

IE3 efficiency motor

allows for continuous operation while reducing energy costs.

Refrigerant dryer

can be added to your GLA for dry, quality air.

Super-silent canopy

reduces sound emissions to a comfortable 57-68 dB(A).

High-quality inverter

Ensures the compressor matches its motor speed to your air demand to give you more reliability and efficiency.



Easy control

The GLA comes with the ES4000 connect controller. It makes your compressor easier to operate, more reliable and more cost-efficient. And thanks to its automatic software updates, your compressor will even get better over time.



- Easy-to-use display
- Connectivity for remote monitoring and control
- DSS advanced energy savings
- Real-time warnings and shutdown alarms
- Service status, history and notifications
- Leakage detection
- Easy pressure band settings via the ICONS app
- Over-the-air software updates

We keep industry running!

Technical specifications

Model	Nominal Pressure	Capacity	Installed Power Motor	Noise Level	Dimensions in mm (LxWxH) / Weight (kg)				
	bar(g)	m³/min FAD*	kW	dB(A)**	Floor mounted	Tank mounted 270l	Tank mounted 270l + dryer	Tank mounted 500l	Tank mounted 500l + dryer
Connection size (BSPP)					G 3/4" F	G 1/2" F	G 1/2" F	G 1/2" F	G 1/2" F
Dimensions (mm)					620x615x950	1540x665x1350		1950x665x1500	
GLA 2	8	0.37	2.2	61	110	180	205	225	250
	10	0.29							
GLA 3	8	0.47	3	61	115	185	210	230	255
	10	0.37							
GLA 4	8	0.6	4	62	120	190	215	235	260
	10	0.52							
GLA 6	8	0.89	5.5	66	130	200	225	245	270
	10	0.78							
GLA 7	8	1.06	7.5	68	140	210	240	255	285
	10	0.98							

Model	Max. working pressure	Reference working pressure	Free Air Delivery @ reference conditions*	Motor power	Noise level measured at 70% load**	Dimensions in mm (LxWxH) / Weight		
	Bar	Bar	m³/min	kW	dB(A)	Floor mounted	Tank mounted 200l	Tank mounted 200l + dryer
Connection size (BSPP)						G 3/4" F	G 1/2" F	
Dimensions mm						620x630x955	1430x600x1265	
GLA2RS	8	7.5	0.14 - 0.36	2.2	57	110	165	190
	10	9.5	0.13 - 0.29					
GLA3RS	8	7.5	0.15 - 0.46	3	57	115	170	195
	10	9.5	0.14 - 0.36					
GLA4RS	8	7.5	0.23 - 0.58	4	58	120	175	200
	10	9.5	0.27 - 0.50					
GLA6RS	8	7.5	0.34 - 0.89	5.5	61	130	185	210
	10	9.5	0.34 - 0.76					
GLA7RS	8	7.5	0.43 - 1.04	7.5	61	140	195	225
	10	9.5	0.42 - 0.96					

* Unit performance measured according to ISO1217, Annex C, latest edition.

** Noise level measured according to ISO2151 2004.

Dimensions are non-binding; refer to drawing.



Reliability



Noise reduction



Energy savings



Simplicity



Geveke
Postbus 820
1000 AV Amsterdam
E-mail : info@geveke.com
T : 020 582 9111